AstroJetTM 2800

AstroJet 2800



- Print Quality up to 600 DPI
- 4" of stitched printing in one pass
- HP-45 Cartridge Technology
- Windows[™] Compatible through Parallel port
- Unique top-load feed mechanism
- Solid Steel Construction
- Available with either easy to use AstroJet® Professional Software or Windows PCL Drivers with AstroPrint™ Imaging Software



Specifications

Print technology: Inkjet, 8 HP 51645A Cartridges Address speed: 26,000/hr - No.10 Envelopes

Print quality: High Quality 600×600 dpi - Standard Quality 600×300 dpi (dots per inch) Letter Quality 600×200 dpi - Draft Quality 600×150 dpi

Image area: 4" X 17"

Print orientation: Normal and Reverse Ink monitor: Visible on display

Fonts: All TrueType fonts available on PC
Prints: Prints graphics, logos and barcodes

Material size: Length – 5" to 17" - Width – 3" to 13.5"

Material thickness: Up to 3/8"

Feeder capacity: Up to 750 No.10 envelopes

Print colors: Standard and Versatile Black, Red, Blue, Green, and Yellow Ink: Water-based. May require drying assistance for coated stock

Software: AstroJet Software for Windows™ 98, 2000 and XP

PC interface: Centronics Parallel or USB with PCL version

Counters: One operator resettable job counter, one permanent lifetime counter Duty cycle: 60 million addresses total or 1,000,000 per month over a 5-year

life cycle

Dimensions: 23" H x 28" L x 22" W (584 mm H x 711 mm L x 559 mm W)

Weight: 80 lbs. (36.4 kg.)

Available models: AstroJet™ 2800 (115VAC) with AstroJet® Professional Software,

AstroJet® 2800 E (220VAC) with AstroJet® Professional Software

Options: Conveyor/Stacker and Drop Tray



CK Business Center 2, rue Léon Laval Z.A. Am Bann L-3372 Leudelange

Tél: +352 26 380-1 Fax: 26 380-380

www.ck-online.lu www.konicaminolta.lu postprint@ck-online.lu