ClearOne®

CHAT® 160 | CHATAttach™ 160

Personal/Group Speakerphones for Skype™

Speakerphones for individual, small, medium and large group use, the CHAT 160 and CHATAttach 160 connect to PCs and laptops for rich, hands-free calls with Skype. The CHAT 160 and CHATAttach 160 are completely full-duplex, contain HDConference® and are the perfect addition to the office or conference room for greatly enhanced collaboration.

DELIVERS SUPERIOR HANDS-FREE AUDIO FOR SKYPE CALLS

APPLICATIONS

Perfect for:
+ Small, medium and large Conference Rooms
+ The Office
+ SOHO

Skype:
+ Incoming calls ring on the CHAT 160 and CHATAttach 160
+ No headset wires or discomfort
+ Plug-and-play operation

Other devices or applications:
+ Internet phone applications
+ Instant messaging applications
+ VoIP softphones
+ Enterprise telephones
+ Web conferencing
+ Audio playback
+ Desktop video conferencing

HDConference®

ADVANTAGES

Provides high quality speakerphone capabilities on PCs or laptops:
+ Connect the CHAT 160 or the CHAT Attach 160 to PCs and laptops via USB for hands-free, full-duplex audio with Skype
+ Hands-free flexibility and comfort:
    > Move around freely without being tethered with a headset
    > Avoid discomfort caused by prolonged headset use
    > Easily includes groups of participants on Skype calls

+ Replaces the PC's speakers and microphone with a high-quality, full-duplex audio solution
+ True plug-and-play operation
+ Crystal-clear audio for video conferencing and streamed multimedia content
+ Sleek industrial design complements the professional environment of any office or meeting room

Enjoy crisp, clear audio:
+ Advanced HDConference audio processing technologies deliver remarkably rich, full audio for natural, effortless conversations:
    > True full-duplex performance allows users to listen and speak at the same time without audio cutting in and out
    > Distributed Echo Cancellation® eliminates acoustic echo
    > Noise reduction identifies and removes ambient room noise
    > First mic priority turns down the microphones that are not in use
    > Advanced automatic level management automatically adjusts microphone levels

+ Three built-in microphones provide full 360-degree coverage up to 8 feet from the speakerphone
    > Easily manage audio for 1-6 call participants
    > Provides rich audio from the far side participants

+ Full bandwidth frequency response delivers better audio

> ## CHAT 160 **COMPONENTS**

> ## CHATAttach **COMPONENTS**

CHATAttach Packout for the CHAT 160

CHAT 160 Unit
Part # 910-156-251

USB 2.0 Connection Cable
Part # 830-156-200

Quick Start Guide
Part # 800-156-251

Two CHAT 160 Units
Part # 910-156-251

USB 2.0 Connection Cable
Part # 830-156-200

CHATAttach Cable
Part # 830-156-010L

CHATAttach Power Supply
Part # 551-156-200

CHATAttach Quick Start Guide
Part # 800-156-225

CHATAttach Expansion Cable Packout

CHATAttach Cable
Part # 830-156-010L

CHATAttach Power Supply
Part # 551-156-200

CHATAttach Quick Start Guide
Part # 800-156-225

Ready to use out of the box

All the components you need to quickly get up and running, including cabling and Quick Start Guide.

> ## ROOM APPLICATIONS

CHAT 160

CHATAttach 160

Configuration Software

Allows users to easily switch between devices; software applies optimized settings to CHAT 160 for each device. Auto-updates from the Web to keep software & CHAT 160 up-to-date with the latest enhancements.

> ## SPECIFICATIONS

System Requirements
Windows XP, Windows Vista or Windows 7

Connections
 USB:
Version 2.0 Compatible
Type: Mini-B Female

 Keyed Connector:
Keyed RJ-45 (8-conductor)

Controls
Volume Up
Volume Down
Microphone Mute

Audio
 Speaker:
Bandwidth: 190 Hz - 20 kHz

Max Output Level:
85 dB SPL @ 1 foot (0.30 meter)

 Microphone
Bandwidth: 50 Hz - 7.75 kHz

Environmental
Operating Temperature:
41 - 104° F (5 - 40° C)

Processing
Full Duplex
Distributed Echo Cancellation (D.E.C.)®
Noise Cancellation (NC)
Automatic Level Control (ALC)
Line Echo Cancellation (LEC) - Selectable
First Mic Priority

Power
 USB:
5 VDC @ 500 mA Maximum

 External:
Input: 100 - 240 VAC
Output: 9 VDC @ 560 mA

Tip: Power
Ring: Ground

Mechanical
Dimensions (W x D x H):
7.4" x 7.4" x 1.8" (18.8 cm x 18.8 cm x 4.6 cm)

Weight:
1.17 lbs (0.53 kg)

Compliance
RoHS
REACH
FCC Class A Part 15
ICES-003
CE Listed
UL Listed

Model Numbers
910-156-251 CHAT 160
• Single CHAT 160 and Connecting Cable

910-156-251-00 CHATAttach 160
• Two (2) CHAT 160 Devices, Connecting Cables and Power Supply

Accessory Part Numbers
910-156-225 CHATAttach Expansion Kit
• Includes Cables, Power Supply and Quick Start Guide to Update Two (2) CHAT 160 Devices to CHATAttach