

HP Latex 335 Print and Cut Solution

Expand—into wider applications with this 64-in true print and cut solution



The HP solution—best in its class¹

- Print more applications, full bleed stickers don't shrink or curl; reach indoor spaces solvent can't
- Enjoy accurate high-speed cutting and cut throughs; LAN connectivity and HP media basket add convenience
- Optimized workflow management from a single point—includes unique software with barcode integration
- Design applications in 3 simple steps—no design skills are needed with HP Signage Suite in box²

True print AND cut

- Print AND cut at the same time—versus print OR cut with solvent—with this reliable, dual-device solution
- Avoid solvent wait time—prints come out dry, cut/laminate right away with no degas time, and deliver same day
- Avoid lamination for short-term applications—scratch resistance is comparable to hard-solvent inks³

Easy, reliable workflow

- Print and cut in 5 simple steps—add cut lines from the RIP, predefined cutting presets, easy user interface
- Efficient job recognition and reliable, errorfree cutting—Optical Positioning System (OPOS) and HP Barcode
- Avoid the complexity of other dualdevices—this complete HP solution is designed to work as one



¹ Based on productivity and environmental advantages compared to the leading (per IDC market share numbers, March 2017) and comparably priced solvent-technology-based integrated print and cut solution. HP internal productivity testing performed February 2017. The HP Latex Print and Cut Solution also uses HP Latex inks that meet UL ECOLOGO® Certification to UL 2801, demonstrating that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see <u>ul.com/EL</u>).

² Requires an HP Applications Center account, Internet connection, and connected Internet-capable device.

³ You can consider unlaminated use for short-term signage with scratch resistance comparable to hard-solvent inks on self-adhesive vinyl and PVC banner. Scratch-resistance comparison based on testing third generation HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

Technical specifications

HP Latex 335 Pri			
Printing	Printing modes	50 m²/hr (538 ft²/hr) - Billboard (2 pass)	
		23 m²/hr (248 ft²/hr) - Outdoor High Speed (4 pass)	
		17 m²/hr (183 ft²/hr) - Outdoor Plus (6 pass)	
		13 m²/hr (140 ft²/hr) - Indoor Quality (8 pass)	
		10 m²/hr (108 ft²/hr) - Indoor High Quality (10 pass)	
		6 m²/hr (65 ft²/hr) - Backlits, Textiles, and Canvas (16 pass)	
		5 m²/hr (54 ft²/hr) - High Saturation Textiles (20 pass)	
	Print resolution	Up to 1200 x 1200 dpi	
	Margins	5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in)	
	Ink types	HP Latex Inks	
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer	
	Cartridge size	775 ml	
	Printheads	6 (2 cyan/black, 2 magenta/yellow, light cyan/light magenta, 1 HP Latex Optimizer)	
	Color consistency ⁴	Average ≤ 1 dE2000, 95% of colors ≤ 2 dE2000	
Media	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paper- based media, backlit polyester film)	
	Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings,	
		canvas, synthetics, (fabrics, mesh, textiles and any other	
		porous materials require a liner)	
	Roll size	254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to	
		64-in) rolls with full support)	
	Roll weight	42 kg (92.6 lb)	
	Roll diameter	250 mm (9.8 in)	
	Thickness	Up to 0.5 mm (19.7 mil)	
Applications		ble clothing, Displays, Exhibition and event graphics, Exterior	
	signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics,		
Connectivity	Wall decals, Window Interfaces (standard		
Dimensions	Printer	2561 x 840 x 1380 mm (101 x 33 x 54 in)	
(w x d x h)	Printer (Shipping)	2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in)	
Weight	Printer	208 kg (459 lb)	
-	Printer (Shipping)	290 kg (639.5 lb)	
What's in the bo	xHP Latex 335 Printer, printheads, maintenance cartridge, printer stand, spind take-up reel, variable front tension kit, user maintenance kit, edge holders, q reference quide, setup poster, power cords		
Environmental		ure 15 to 30°C (59 to 86°F)	
ranges			
	Operating humidity	20 to 80% RH (non-condensing)	
Acoustic	Sound pressure	55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep)	
	Sound power	7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)	
Power	Consumption	2.6 kW (printing); 72 watts (ready); < 2.5 watts (sleep)	
	Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 3 A max per printer power cord; 16 A max per curing power cord	
Certification	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and	
		Kazakhstan (EAC); Australia and New Zealand (RCM)C)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)	
	Environmental	ENERGY STAR, WEEE, RoHS (EU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT Bronze, OSHA, CE marking compliant	
Warranty	One-year limited ha	rdware warranty	
HP Latex 64 Cut			
Cutting	Cut type	Drag-knife with TurboCut and Tangential emulation modes	
	Cut width	158 cm (62.2 in)	
	Cut speed	Up to 113 cm/sec (44 in/sec) diagonal	
	Acceleration	Up to 3 G diagonal	
	Accuracy	0.2% of movement or 0.25 mm, (0.01 in) whichever	
		is greater	

is greater

±0.1 mm (0.004 in)

optional sandblast blade

two wires and per printer		For the entire HPLFMedia.c	e HP Large Format Printing Materials portfolio, please see om.
a (CSA listed); larus, and RCM)C) : USA (FCC lia and New	Service and support	U9PN8E	HP 2 year Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support
		U9PN9E	HP 3 year Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support
		U9PP2PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support

Connectivity

Dimensions

(w x d x h)

Warrantv

Product

Accessories

Original HP

printheads

Original HP ink

cartridges and

maintenance

supplies

Original HP

printing materials

large format

Weight

Interfaces (standard)

Cutter (Shipping)

Cutter (Shipping)

authorized reseller Ordering information

Cutter

Cutter

(set of 2)

1LH37A

1UP26A

1UP27A

1UX44A

1UX45A

EOM56A

F0M58A

EOM59A

CZ677A

CZ678A C7679A

CZ680A

CZ682A

CZ683A

CZ684A

CZ685A

CZ686A

CZ687A

CZ706A

CZ681A

USB and Ethernet (LAN)

software, quick reference guide, setup poster, documentation software, power cords, standard holder (1), standard blades (2), cut-off knife (1), 3-in media flanges

HP Latex 335 Print and Cut Solution

HP Latex 64-in Printer 2-in Spindle

HP Latex 64-in Printer 3-in Spindle

HP 831 Cyan/Black Latex Printhead

HP 831 Latex Optimizer Printhead

HP Latex 300/500 User Maintenance Kit

HP 831 Yellow/Magenta Latex Printhead

HP 831A 775-ml Black Latex Ink Cartridge

HP 831A 775-ml Cvan Latex Ink Cartridge

HP 831A 775-ml Magenta Latex Ink Cartridge

HP 831A 775-ml Light Cyan Latex Ink Cartridge

HP 831 775-ml Latex Optimizer Ink Cartridge

HP printing materials are designed together with HP Latex Inks and HP Latex printers to provide optimal image quality, consistency, and reliability.

HP 831 Latex Maintenance Cartridge

HP PVC-free Durable Smooth Wall Paper REACH,⁵ FSC[®] certified,

HP Permanent Gloss Adhesive Vinyl REACH⁵

HP Backlit Polyester Film 🛟

UL GREENGUARD GOLD Certified⁸ HP Premium Poster Paper 🛟 FSC® certified

HP 831A 775-ml Light Magenta Latex Ink Cartridge

HP 831A 775-ml Yellow Latex Ink Cartridge

HP 831 Light Magenta/Light Cyan Latex Printhead

HP Latex Cutter Extended Kit

HP Latex 2-in Media Holder Kit

HP Latex Standard Blade Kit

HP Latex Specialty Blade Kit

One year, after the HP Latex End of Installation Registration is completed by an HP

54 ka (119 lb)

78 kg (172 lb) What's in the boxHP Latex 64 Cutter, cutter stand, HP FlexiPrint and Cut RIP, HP Cutter Control

1980 x 680 x 1145 mm (77.9 x 26.8 x 45.1 in)

2110 x 480 x 670 mm (83.1 x 18.9 x 26.4 in)

U9PP3PF HP 2 year Post Warranty Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support The color variation inside a printed job has been measured to be within this limit: maximum color difference (95% of colors) ≤ 2 dE2000. Reflective measurements on a 943 color target under CI standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products.

HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia.com/hp/ecosolutions for details.

BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions.

UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <u>ul.com/gg</u> or <u>greenguard.org</u>.



© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice.

0 to 400 grams of downforce, in 5-gram steps

0.05 to 0.25 mm (0.002 to 0.01 in); 0.8 mm (0.03 in) with

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.



4AA6-9612ENA, September 2017

Repeatability

Cut thickness

Cut force