PRODUCT SPECIFICATION 1/2



Tourguide 2020-D HDE 2020-D-II



The HDE 2020-D stethoset TourGuide receiver is comfortable to wear and integrates both the receiver and headphones. The powerful battery ensures up to 8 hours operating time.

The stethoset receiver automatically deactivates itself the moment that it is taken off, thus battery life will be preserved. Tour participants will be able to individually adjust the volume through a rotary control on the receiver, without the need to even take the device off.

The LC display provides information of volume, battery status, quality of reception and the channel being listened to. Channels can easily be set and adjusted by using the middle buttons.

DELIVERY INCLUDES

- HDE 2020-D-II
- Instruction manual

SPECIFICATIONS

Modulation	2 FSK	
Frequency range	863 – 865 MHz	
Frequency range (US)	926 – 928 MHz	
Channels Tourguide mode: Conference mode:	6 in parallel 8 in parallel	
AF frequency response	100 – 7,000 Hz	
Headphone output power	-	
Min. headphone impedance	32 Ω	
THD at 1 kHz	< 1 %	
Operating time	typ. 8 h	
Power supply	Lithium-Polymer recharge- able battery, 830 mAh	
Temperature range	0 – 50 °C	
Dimensions	245 x 125 x 20 mm	
Weight	approx. 73 g	

PRODUCT VARIANTS

HDE 2020-D-II-US Art. no. 504797 HDE 2020-D-II Art. no. 504796

FEATURES

- Digital RF signal reception
- · Intuitive operating concept
- 8 hours battery life
- Sturdy earbows
- Backlit LC display
- Large rotary volume control

ACCESSORIES

EZL 2020-20 L	Charging case	Art. no. 500542
L 2021-40	19" charger rack	Art. no. 502037
OP - HDE 2020	Earbuds, black	Art. no. 531435
OP - HDE 2020-D	Earbuds, lumine- scent	Art. no. 520379

PRODUCT SPECIFICATION 2/2



Tourguide 2020-D HDE 2020-D-II

DIMENSIONS







