MA-808 Portable Wireless PA System

Key Features

- Lightweight Class-D amplifier produces 267-watt audio output.
- Industry's only master level control enables volume be wirelessly controlled by an optional ACT-32HR transmitter microphone instead of a separate remote.
- Master volume with "Memory" and "Standard" mode options. "Memory" mode saves and recalls last volume level during next power on. "Standard" mode resets to zero level. Up to 4 optional diversity receiver modules with 16 auto-scannable frequencies One-touch Scan & ACT sync button for fast and easy channel set-up. •
- .
- •
- Built-in Bluetooth music player for wireless audio streaming.
- Retractable handle and sturdy wheels for easy transport. • Built-in storage compartment for 2 HH or BP transmitters.
- •
- ٠
- A voice priority feature that mutes the music when wireless microphone is used. Built-in AC switching power supply for universal usage and fast battery charge. A smart 4-segment battery meter for accurate battery reading and charging status.
- Industry's only MTM-92 transmitter option for interlinking multiple MA-808 portables wirelessly to • extend transmission range & expand coverage.
- Optional lithium rechargeable battery pack for direct replacement of existing battery.
- Speakon extension speaker output (use with MA-808EXP).
- 3 power modes: AC, rechargeable battery and DC jack. Suitable for tripod, floor or desk mount.
- •

Transmitters & Microphones

ACT-32H 32HR 32HC	Handheld Transmitter for MRM-70B MRM-72B
ACT-32T ACT-32TC	Bodypack Transmitter for MRM-70B MRM-72B
VT-22 ST-32 ET-32	Instrument Transmitter for MRM-70B MRM-72B
ACT-24HC ACT-24TC	Handheld Bodypack Transmitter for MRM-24
ST-24 ET-24 MT-24 DM-100	Instrument Transmitter for MRM-24
ACT-70H 70HC 70T 70TC	Handheld & Bodypack Transmitter for MRM-70W
ACT-80H 80HC 80T 80TC	Handheld & Bodypack Transmitter for MRM-80
MM-107 MM-39 MM-59	Wired Supercardioid Dynamic Microphone

Accessories

MB-70	Sealed Lead-acid Rechargeable Battery. (12V, 4.5AH)
MB-80	Lithium Iron Phosphate (LFP) Rechargeable Battery (12.8V)
SC-80	Storage Cover Bag
MS-70	Tripod Speaker Stand
MA-808EXP	Passive Extension Speaker
MRM-24	2.4 GHz Digital True Diversity Receiver Module
MRM-70B	Single-Channel Diversity Receiver Module
MRM-72B	Dual-Channel Diversity Receiver Module
MRM-70W	Wideband Single-Channel Diversity Receiver Module
MRM-80	Digitally Encrypted Single-Channel Diversity Receiver Module
MTM-92	Wireless Interlinking Transmitter Module

Technical Specifications

Portable PA	
Max. Power Output	267 W: 190W (woofer) 77W (tweeter)
Amplifier	Class D & Class AB
Sensitivity	Typical: 96 dB Maximum: 111 dB
T.H.D.	<1%
Frequency Response	50 Hz – 18 kHz
Speaker	Tweeter: 1.5" Compression Driver; Woofer: 10" Neodyium
Audio Inputs	Wired: XLR×1 & 6.3mm (1/4")×1; Wireless: UP to 4 wireless microphones; Line-In: Unbalanced RCA jack
Bluetooth Connectivity	Yes
Audio Output	Unbalanced line RCA jack
Extension Speaker	Speakon output
Master Volume Control	Manually or Wirelessly via ACT-32HR
Controls	Tone, Voice Priority & Echo on wireless mics
Storage	2 handheld or bodypack transmitters
Installation	Speaker stand, flat surface or retractable handle & wheels
Power Supply	AC: Built-in 100 – 240 V AC switching power supply (Max. Power Consumption: 352 W) DC & Battery: 24 – 32 V DC, 12V/4.5AH rechargeable gel cell battery (MB-70× 2) or optional MB-80×2
Charge Time	8 hours (automatic charging management)
Stand-by Time	> 6 hours
Battery Indicator	4-level Indicator (25 50 75 100%)
Color	Black
Dimensions (W × H × D)	360 × 560 × 350mm 14.2 × 22 × 13.8"
Weight	Approx. 20.5 kg 45 lbs (MB-70 batteries included)
	Wireless System (optional)
Receiver	1 or 2 MRM-70B MRM-72B MRM-70W MRM-80 MRM-24
Max. Receiver	Up to 4
Frequency Range	MRM-70B MRM-72B MRM-70W MRM-80: UHF 480 – 934 MHz (country dependent) MRM-24: 2.4 GHz
Installation	Plug-in Module
Antenna	Built-in
	Audio Player (optional)
Model	CDM-2 DPM-3
Installation	Plug-in Module











