

SCANSNAP ix1300



Connect your worlds with one touch.

Balance size and performance

"Just the right fit" to keep life organized

ScanSnap iX1300 is the compact, yet powerful solution to all your daily and ad-hoc scanning needs. At home, in the office, or even within your remote workspace, the device takes the pain out of scanning so that you are well on your way to quick and easy digitization, the moment you need it.



Get right into new ways of working and scanning

Two ways to scan to match your documents and environment

No need to worry about saving space for documents using U-turn Scan. Equipped with a new ADF (Automatic Document Feeder) for ejecting scanned paper to the top of the scanner, sit back and relax as scanning proceeds with just a practical space of A4 size or smaller required.





Use Return Scan, to read a wide variety of documents, even feeding manually one by one while multi-tasking at work. The iX1300 feeds and ejects documents from the front, making it a breeze to scan documents like folded paper, business cards, receipts, photographs, and postcards, without having to make any adjustments.

Scan almost anywhere

Use the iX1300 to scan in any location with Wi-Fi. 2.4/5 GHz¹ support allows stable wireless scanning as an added plus to USB. In environments where Wi-Fi is available, ScanSnap Cloud¹ works with a variety of cloud services to save documents to all your favorite cloud services on a simple touch of the button. Images are optimized and sorting absolutely, fuss-free with a host of automated functions. Bring along your AC cable, and the iX1300 is sure to be the right fit with superb performance.

ScanSnap iX1300

Handy, convenient, but powerful

Simplicity makes the experience beautiful

The iX1300 comes with just one button, so that you can perform all your scanning tasks with the ScanSnap-favorite "one touch". Keep digitization processes simple, while boosting efficiency.

Faster scanning for bigger batches

Productivity is never placed second in priority with ScanSnap. The iX1300 thrives at 30 ppm and holds up to 20 sheets, doubling the capacity of its predecessor. Scan both sides of batches up to 20 documents in less than 40 seconds for speedy and hassle-free digitization.

Ready to scan right away

Get ready for revolutionary scanning with a single action. One single action to open the cover and bring the iX1300 to life. The extension slides out on opening of the cover, so that all you need to do, is place your documents and press the Scan button for clean and optimized images.

Daily ad-hoc scanning can be carried out with the cover closed as well. No need to power the scanner on yourself, as it awakens on feeding documents from the front.



The all-in-one solution for document management



ScanSnap Home (for PC) is a total document management software specially designed for ScanSnap scanners. Easily manage, edit, and utilize scans, all in one application.

Accommodates any scanning environment

- Create profile icons to preset save-to destinations, cloud services, color settings and much more
- Save as PDF, Searchable PDF, and JPEGcreate searchable PDF files in a matter of seconds with scanning and OCR processing happening simultaneously
- Use the Quick Menu to decide where to save after scanning

Easy and convenient

Post-scan processes shouldn't be a hassle. The software recognizes documents and groups by type (documents, receipts, business cards, photos), and enables document search using folders, tags, and keywords.

ScanSnap Home (for mobile)



An application dedicated to mobile devices is also available.

General Specifications

olor mode		ADF (Automatic Document Feeder)/Manual Feeder, Duplex Color, Grayscale, Monochrome,	
		I Color Craycoalo Monochromo	
		Automatic (Color/Grayscale/Monochrome*1 detection)	
or e		CIS x 2 (Front x 1, Back x 1) 3 Color LED (Red/Green/Blue)	
		600 dpi for Color or Grayscale, 1200 dpi for Monochrome	
Sidelon	Auto mode		
	(Default)*3	Simplex/Duplex: 30 ppm	
		Simplex/Duplex: 30 ppm (Color/Grayscale: 150 dpi, Monochrome: 300 dpi)	
scan	Better	Simplex/Duplex: 30 ppm (Color/Grayscale: 200 dpi, Monochrome: 400 dpi)	
(ADF)		Simplex/Duplex: 30 ppm	
		(Color/Grayscale: 300 dpi, Monochrome: 600 dpi) Simplex/Duplex: 9 ppm	
	mode"1"4	(Color/Grayscale: 600 dpi, Monochrome: 1,200 dpi)	
	Auto mode (Default)*3	5 seconds (Color/Grayscale: 150 dpi, Monochrome: 300 dpi)	
	Normal	5 seconds	
		(Color/Grayscale: 150 dpi, Monochrome: 300 dpi)	
		5 seconds (Color/Grayscale: 200 dpi, Monochrome: 400 dpi)	
Feeder)		5 seconds	
		(Color/Grayscale: 300 dpi, Monochrome: 600 dpi)	
	Excellent mode ^{11*4}	14 seconds (Color/Grayscale: 600 dpi, Monochrome: 1,200 dpi)	
U-turn scar		Minimum: 50.8 x 50.8 mm (2 x 2 in.) Maximum: 216 x 355.6 mm (8.5 x 14 in.)	
Return sca	n	Minimum: 50.8 x 50.8 mm (2 x 2 in.) ⁻⁷	
(Manual Fe	eder)	Maximum: 216 x 355.6 mm (8.5 x 14 in.)	
		Minimum: 25.4 x 25.4 mm (1 x 1 in.)	
		Maximum: 127 x 178 mm (5.0 x 7.0 in.)	
	er Sheet	Minimum: 25.4 x 25.4 mm (1 x 1 in.) Maximum: 297 x 431.8 mm (11.69 x 17 in.)	
	det Carrier	Minimum: 25.4 x 25.4 mm (1 x 1 in.)	
		Maximum: 150 x 195 mm (5.9 x 7.67 in.)	
Long PC		3,000 mm (863 mm in 32-bit)*8	
scarining		Simplex: 1,117 mm 40 to 128 g/m² (11 to 34 lb)	
		A8 size or less: 128 to 209 g/m² (34 to 56 lb) A6 size or less: 40 to 209 g/m² (11 to 56 lb)	
ht			
)	Return scan	Paper: 20 to 413 g/m² (5.4 to 110 lb) Booklets: 2 mm (0.08 in.) or less ⁻¹	
		Cards: 1.4 mm (0.06 in.) or less*9	
	, eeuer)	(Includes embossed cards)	
ity* ¹⁰		20 sheets (A4, 80 g/m² or 20 lb)	
	USB	USB 3.2 Gen1x1 / USB 2.0 / USB 1.1 (Connector Type: Type-B)*	
	Wi-Fi	IEEE802.11a/b/g/n/ac Frequency band: 2.4 GHz / 5 GHz ¹¹²	
		Access Point Connect Mode (Infrastructure mode)*15	
ace		Direct Connect Mode (Ad-hoc mode)*14	
irement		AC 100 to 240 V, 50/60 Hz	
	Operating	17 W or less	
		17.14/	
		1.7 W or less	
n	(Wi-Fi	2.0 W or less	
	connection)		
	Standby mode	0.3 W or less	
Operation environment		Temperature: 5 to 35 °C (41 to 95 °F)	
Dimensions (W x D x H)*15 Device weight		Relative humidity: 20 to 80% (Non-condensing)	
		296 x 114 x 87 mm (11.7 x 4.5 x 3.4 in.) 2.0 kg (4.4 lb)	
ght	ince		
	ince	ENERGY STAR/RoHS Length detection	
ght ntal complia	ince	ENERGY STAR/RoHS	
	Return scan (Manual Feeder) U-turn scal Return sca (Manual Feeder) With Photo Sheet (Op With Carri (Option)" Sheet (Option)"	Auto mode (Defaulty)** Normal mode Best mode Excellent mode** Auto mode (Defaulty)** Return scan (Manual Feeder) With Photo Carrier Sheet (Option)*** With Booklet Carrier Sheet (Option)*** Long paper scanning** U-turn scan (Manual Feeder) With Photo Carrier Sheet (Option)*** With Booklet Carrier Sheet (Option)** Long paper scanning** U-turn scan (Manual Feeder) With Booklet Carrier Sheet (Option)** With Booklet Carrier Sheet (Option)** U-turn scan (Manual Feeder) Int Return scan (Manual Feeder) Int Sleep mode (USB connection) Sleep mode (USB connection) Standby mode	

Tinacus: Support TWAIN**

1**Feature is unavailable when using ScanSnap Connect Application**: 2 Scanning speeds may vary due to the system environment. For details, please visit our website at: https://www.pfu.ricoh.com/global/scanners/scansnap/. *3 Scans will be performed in 300 dpi (Color/Grayscale) or 600 dpi (Monochrome) if shorter sides are less than 105 mm, and in 200 dpi (Color/Grayscale) or 400 dpi (Monochrome) if shorter sides exceed 105 mm. *4 Feature is unavailable when using ScanSnap Cloud. *5 Carrier sheet scanning is only supported when scanning documents in Return scan (Manual Feeder). *6 Long page scanning (Color/Grayscale: 200 dpi, Monochrome: 400 dpi) is only supported when scanning documents in U-turn scan (ADF). When using ScanSnap Connect Application and ScanSnap Cloud, scans are performed in Color/Grayscale: 200 dpi, Monochrome: 400 dpi). *7 43, 84, 11x 17 in. documents is uses are required to be folded in half. *8 Scanning in "Excellent mode" is supported with documents of up to 360 mm. *9 Compliant with 17ye BC07810 D-1. *10 Maximum capacity varies, depending upon paper weight. *11 Some computers do not recognize the ScanSnap when it is connected to a USB 3.2 Gentil Connect Mode erequires a Wi-Fi access point or router. *145 GHz Wi-Fi is not available with Direct Connect Mode. *15 Excluding the stacker and other external attachments.

Consumables

Description	Part number	Remarks	
Pick Roller*1	PA03805-0021	Lifetime: Every 100,000 sheets or one year	
Pad Unit*1	PA03805-0022	Lifetime: Every 30,000 sheets or one year	
Cleaner F1	PA03950-0352	100 ml bottle For use on the Pad unit and Pick roller	
Cleaning Wipe	PA03950-0419	24 packets For use on the Pad unit and Pick roller	
Cleaning Paper	CA99501-0012	10 sheets Use this non-woven sheet with Cleaner F1	

Options

Options			
Description	Part number	Remarks	
Carrier Sheets*1	PA03360-0013	Contains 5 sheets supporting photographs and various document sizes For ScanSnap iX1300, iX1600, iX1400, iX1500, iX100, S1100i	
Photo Carrier Sheets	PA03770-0015	Contains 3 sheets supporting photographs (E-size, L-size, King-size), postcards, and business cards	
Booklet Carrier Sheet	PA03795-0018	Contains 1 sheet supporting booklets	
ScanSnap Soft Case M	PA03805-0002	Stores the ScanSnap iX1300 and accessories	

^{*1} Although ScanSnap Carrier Sheets have a listed lifespan of 500 scans, the lifespan may vary with usage. ScanSnap Carrier sheets are intended to scan paper documents with weights of 209 g/m² or less. They also support the scanning of folded documents that are as large as 216 x 297 mm.

ScanSnap iX1300 System Requirements

Windows

	Operating systems		Windows 11 (64-bit) Windows 10 (32-bit / 64-bit)* ^{1*2}	
	Hardware requirements*3	CPU*4	Intel or Intel-compatible processors	
		Display resolution	1,024 x 768 pixels or more	
		Disk capacity*5*6	3.8 GB or more of free disk space	

[&]quot;I ScanSnap scanners do not run with Windows II and I0 ARM-based PCs. "2 Operate Windows in desktop mode.
"3 The ScanSnap device may not work if the connected computer does not meet these requirements. "4 Scanning speeds may vary due to the system environment. "5 Indicated disk capacity requirements apply when downloading ScanSnap Home (for PC). "6 NET Framework 4.8 or later must be installed. If it is not installed, it is installed with ScanSnap Home (for PC) up to 4.5 GB of disk space is required for the installation." Please refer to the ScanSnap website for the latest support information of the driver and applications. Compatibility may differ depending on the software's version. "The system requirements may change depending on the support policies of the above system and third-party software."

Mac

	Operating systems		macOS Catalina 10.15 or later	
	Hardware requirements*1	CPU*2*3	Intel processor or Apple silicon	
		Display resolution	1,024 x 768 pixels or more	
		Disk capacity	2.5 GB or more of free disk space	

[&]quot;The ScanSnap device may not work if the connected computer does not meet these requirements. "2 The ScanSnap device also operates with Apple Silicon-based Mac computers. Please visit the ScanSnap website for latest support information." 3 Scanning speeds may vary due to the system environment. "Compatibility may differ depending on software versions. Please visit the ScanSnap website for latest information on driver and application support. The system requirements may change depending on the support policies of the above system and third-party software.

Other Devices

iOS/iPadOS	iOS 15 or later/iPadOS 15 or later		
Android™/ChromeOS	Android 9 or later/ChromeOS 115.0.5790.182 or later		

^{*} Wi-Fi environment is required.

Software

	Windows	Mac	iOS/iPadOS	Android™/ChromeOS
	ScanSnap Home (for PC)*1		ScanSnap Home (for mobile)	
ı	ABBYY FineReader for ScanSnap™		-	_

Accessories

•Safety Precautions •AC Cable •AC Adapter •USB Cable

This scanner is designed to digitize materials that can be reproduced lawfully, in accordance with applicable copyright regulations and other laws. ScanSnap users are responsible for how they use this scanner. It is imperative that ScanSnap users comply with all applicable local rules and laws, including, without limitation, copyright laws when using this scanner.

*ABBYY** FineReader** Engine © ABBYY. OCR by ABBYY. ABBYY and FineReader are trademarks of ABBYY Software. Ltd. which may be registered in some jurisdictions. *Android and Chrome OS are trademarks or registered trademarks of Google LLC. Thick is a trademark of Intel Corporation or its subsidiaries. "ISIS is a trademark of Open Text. "Mac, macOS, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. *Microsoft and Windows are trademarks of the Microsoft group of companies. *ScanSnap, the ScanSnap logo and ScanSnap Home are registered trademarks of trademarks of PEU Limited. "Other company names and product names are the trademarks or registered trademarks of the respective companies.



PFU Limited has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are trademarks or registered trademarks of the U.S. Environmental Protection Agency.



Be sure to carefully read all safety precautions prior to using this product and use this device as instructed.

Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product.



Tél. +352 26 380 1 technologies 2, rue Léon Laval L-3372 Leudelange sales@ck.lu | ck-officetechnologies.lu

¹ These recommended lifetimes are for 80 g/m 2 (20 lb) A4 sized documents. Therefore, appropriate replacement lifetimes may vary for other document types.

1t is recommended to use original or approved accessories for consumables, options and cleaning kits, specially designed for your device. Device failures, troubles and damages arising from use of OEM or 3rd Party accessories may render your warranty invalid and incur charges for repair even during the warranty period.