Image Scanner

RICOH fi-7900 Datasheet

☑ Scanner



Advanced productivity for high-volume scanning

The fi-7900 scans A4 landscape documents at high speeds of 140 ppm/280 ipm (200/300 dpi). It is capable of scanning up to A3 sized portrait documents and can load up to 500 sheets at a time.

Accurate feeding to maximize productivity

Our production scanners are designed to build productive workflows. In addition to our reliable feeding, the fi-7900 comes with a variety of functionalities that make feeding performance even better. Finish scanning faster without the need to make any rescans, using the all-new Automatic Separation Control function. This new function automatically calibrates torque on the brake rollers and guarantees that documents go through one at a time. The fi-7900 now also comes with the fi Series signature Skew Reducer function providing independent separator rollers to ensure skewed documents do not affect documents to follow.

Organized paper output for clean and fast workflows

Not only do we ensure that paper is fed through smoothly but also that output is made in neat stacks. The improved Stacking Control function and Elevator Stacker allow operators to quickly gather documents after scanning so that operators can quickly move on to the next batch, and scan multiple batches in shorter times.

Stress-free usability with an operator-friendly design

The fi-7900 is designed to make the operator experience easy. Operators can scan directly from the scanner with the job-registration function, and complete various operations on the easily-accessible operator panel and LCD status display. Ease of use also applies to routine maintenance of the scanner. The fi-7900's LED lights make cleaning dust, debris, and ink residue build-up from the glass simply easy and stress-free.

Advanced software for maximized efficiency

Empower operator workflows and feed information efficiently with our latest PaperStream IP scanner driver and integrated software. With a few simple setting configurations, Automatic Profile Selection allows documents to undergo image processing appropriate to each document format. Operators no longer need to sort documents manually since the driver works with PaperStream Capture to link document formats to specific saving destinations. Image processing functionalities are also enhanced with Advanced Cleanup Technology providing strong character recognition and image cleanup functionalities for better OCR accuracy. All these functionalities work together to offer a wider variety of batch scanning features and assist operator workflows.

Technical Information

recrimical imformation	l			
Scanner Type	ADF (Automatic Document Feeder) / Manual Feed,			
	Duplex			
Scanning Speed*1				
(A4 Landscape)	Simplex: 140 ppm (200/300 dpi) Duplex: 280 ipm (200/300 dpi)			
(Color*2/Grayscale*2/				
Monochrome*3)				
Scanning Speed*1				
(A4 Portrait)	Simplex: 105 ppm (200/300 dpi)			
(Color*2/Grayscale*2/	Duplex : 210 ipm (200/300 dpi)			
Monochrome*3)				
Image Sensor Type	Color CCD x 2 (front x 1, back x 1)			
Light Source	White LED Array x 4 (front x 2, back x 2)			
Optical Resolution	600 dpi			
Output Resolution*4				
(Color / Grayscale /	50 to 600 dpi (adjustable by 1 dpi increments),			
Monochrome)	1,200 dpi (driver)*5			
Output Format	Color: 24-bit, Grayscale: 8-bit, Monochrome: 1-bit			
Background Colors	White / Black (selectable)			
Document Size				
Maximum	304.8 x 431.8 mm (12 x 17 in.)			
Minimum	52 x 74 mm (2 x 3 in.)			
Long Page Scanning*6	5,588 mm (220 in.)			
Paper Weight (Thickness)				
A4 to A5 Size	20 to 209 g/m² (5.4 to 56 lb)			
Less than A5 Size /	41 to 209 g/m² (11 to 56 lb)			
Over A4 Size				
ADF Capacity*7	500 sheets (A4 80 g/m² or Letter 20 lb)			
Expected Daily	120,000 sheets			
Volume*8				
Multifeed Detection	Overlap detection (Ultrasonic sensor),			
	Length detection			
Paper Protection	Lag detection			
Interface	USB 2.0 / USB 1.1			
Power Requirements	AC 100 to 240 V ±10 %			
Power Consumption				
Operating Mode	200 W or less			
Sleep Mode	3.2 W or less			
Auto Standby (Off)				
Mode	Less than 0.3 W			
Operating Environment				
Temperature	5 to 35 °C (41 to 95 °F)			
Relative Humidity	20 to 80% (non-condensing)			
	· · · · · · · · · · · · · · · · · · ·			

Environmental		T			
Compliance	ENERGY STAR®,	ENERGY STAR®, RoHS			
Dimensions*9		460 x 430 x 310 mm (18.1 x 16.9 x 12.2 in.)			
(Width x Depth x	460 x 430 x 310				
Height)					
Weight	32 kg (70 lb)				
Supported	Windows® 11*10	Windows® 11*10, Windows® 10*10,			
Operating System	Windows Server	Windows Server® 2022, Windows Server® 2019,			
	Windows Server	Windows Server® 2016			
Software / Drivers	ers PaperStream IP Driver (TWAIN/TWAIN x64/ISIS),				
	WIA Driver*11, Pa	WIA Driver*11, PaperStream Capture,			
	PaperStream Clic	PaperStream ClickScan*12, Software Operation Panel,			
	Error Recovery G	Error Recovery Guide, Scanner Central Admin Server			
Image Processing	Multi image out	Multi image output, Automatic color detection, Blank			
Functions	page detection,	page detection, Static threshold, Dynamic threshold			
	(iDTC), Advance	(iDTC), Advanced DTC, SDTC, Error diffusion, Dither,			
	De-Screen, Empl	De-Screen, Emphasis, Dropout color (None/Red/			
	Green/Blue/Whit	Green/Blue/White/Saturation/Custom), sRGB output,			
	Hole punch rem	Hole punch removal, Cropping, Index tab cropping,			
	Split image, De-	Split image, De-Skew, Edge correction, Vertical streaks			
	reduction, Chara	reduction, Character extraction, Background pattern			
	removal, Autom	removal, Automatic profile selection			
Included Items	AC cable, USB c	AC cable, USB cable, Setup DVD-ROM			
Options					
Post Imprinter	DA 03575 D 204	Front side printing on degree out			
(FI-680PRF)	PA03575-D201	Front-side printing on document			
Post Imprinter	PA03575-D203	Dock side printing on decurrent			
/	PAU35/5-D2U3	Back-side printing on document			

	rost implifitel	PA03575-D203	Back-side printing on document		
	(FI-680PRB)	1703373 0203			
	PaperStream Capture Pro	PA43404-A695	PaperStream Capture Pro		
	Scan Station (MV)		optional license		
Consumables					
	Pick Roller	PA03575-K011	Every 600,000 sheets or one year		

Separator Roller PA03800-K012 Every 600,000 sheets or one year Brake Roller PA03575-K013 Every 600,000 sheets or one year 4,000,000 printed characters or CA00050-0262 Print Cartridge

*1 Scanning speeds may vary due to the system environment. For details, please visit our website at: https://www.pfu.ricoh.com/global/scanners/fi/. *2 Indicated speeds are from using JPEG compression. *3 Indicated speeds are from using TIFF CCITT Group 4 compression. *4 When scanning in high resolutions (600 dpi or above), scanning may be rejected depending on scanning mode, document size, memory size, and application program. Selectable maximum resolution may vary depending on the length of the scanned document. *5 Limitations may apply to the size of documents that can be scanned, depending on system environment, when scanning at high resolution (over 600 dpi). *6 Documents between 431.8 mm (17 in.) and 863 mm (34 in.) in length are limited to 400 dpi. Documents between 863 mm and 3,175 mm (125 in.) in length are limited to 300 dpi. *7 Maximum capacity depends on paper weight and may vary. *8 Numbers are calculated using scanning speeds and typical hours of scanner use, and are not meant to guarantee daily volume or unit durability. *9 With the ADF hopper closed. *10 fi Series scanners do not run with Windows* 11 and 10 ARM-based PCs. *11 Functions equivalent to those offered by PaperStream IP may not be available with the WIA Driver. *12 Refer to the fi Series Support Site for driver/software downloads and full lineup of all supported operating system versions.

ISIS is a trademark of Open Text. Microsoft, Windows, and Windows Server are trademarks of the Microsoft group of companies. Any other products or company names appearing in this document are the trademarks or registered trademarks of the respective companies

Safety Precautions

Be sure to carefully read all safety precautions prior to using this product and use this device as instructed. Do not place this device in wet, moist, steamy, dusty or oily areas. Using this product under such conditions may result in electrical shock, fire or damage to this product. Be sure to limit the use of this product to listed power ratings.

PFU Limited has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR® is a registered trademark of the United States.



Tél. +352 26 380 1 2, rue Léon Laval L-3372 Leudelange sales@ck.lu | ck-officetechnologies.lu

6 months after opening the bag

Page 2 of 2 2023.11 7900-7.0